



ADORMAT PLUS

PRODUCT DESCRIPTION:

IT IS A HIGH QUALITY MATTE PLASTIC PAINT BASED ON ACRYLIC COPOLIMERIC RESINS AND HIGH RESISTANT AND STRENGTH PIGMENTS TO THE LIGHT, OFFERING A EXTREME WHITE, WASHABLE AND COATED FINISHING. APPROPRIATE FOR INTERNAL AND EXTERNAL DECORATION.

TECHNICAL CHARACTERISTICS:

COLOUR:	WHITE
FINISHING:	MATTE
DILUTE:	WATER
DENSITY:	1,5 gr/c.c. APPROX
VISCOSITY:	20.000-30.000 C.P.S.
TACT DRYING:	30 MIN. APPROX
PERFORMANCE:	12/ 14 m ² / LTR. ACCORDING TO SURFACE CONDITIONS
COATING:	>90%
RE-PAINTING:	2-4 HOURS AFTER APPLICATION
WASHABILITY:	EXCELLENT ACCORDING TO DIN 53778 SPECIFICATIONS
PACKAGING:	3 & 14 LTRS LITHOGRAPHED IML PLASTIC
WAREHOUSING:	18 MONTHS IN NORMAL TEMPERATURES AND CONDITIONS

PROPERTIES:

EXCELLENT APPLICATION WITH BRUSH AND ROLLER GIVING A GOOD FINISHING AND PAINT LEVELLING. VERY RESISTANT TO ABRASION, HUMID FRICTION AND ALKALINITY.

APPLICATIONS:

VERY APPROPRIATE FOR INTERNAL AND EXTERNAL SURFACES PROTECTION AND DECORATION, OFFERING A GREAT PRESERVATION AND EXTREME WHITE MATTE FINISHING.

USE METHOD:

APPLY ON DRY AND CLEAN SURFACES, W/O RUST, DUST, GREASE, HUMIDITY, SALTPETRE, ETC.. OLD SURFACES HAVING BAD CONDITION PAINTS MUST BE FIRST TOTALLY CLEANED TO ENSURE THE RIGHT ADHESIVENESS ON THEM. DO NOT APPLY AT TEMPERATURES BELLOW 5°C OR OVER 35°C.

REV. 02.06.11

With this technical card, based on our experience and research, we only pretend to inform and advise you according to our knowledge and good faith, In any case we can not be responsables for the use of this product under circumstances and conditions of its application, due to be out of our own control.

. Crta. Nacional 301- km.215.700
02630 La Roda (Albacete) Spain
Ph.: +34 967 44 38 38- Fax: +34 967 44 38 14
info@pinturasadoral.com
www.pinturasadoral.com