



WHITE SNOW INCAKRIL

PRODUCT DESCRIPTION:

BREATHABLE MATTE PLASTIC PAINT PRODUCED WITH NATURAL CHARGES AND ACRYLIC – STYRENE RUBBER RESINS, OFFERING HIGH COVERING AND WHITE INTERNAL FINISHINGS.

TECHNICAL CHARACTERISTICS:

COLOUR:	WHITE
FINISHING:	GLOSSY
SOLVENT:	WATER
DENSITY:	1.7 gr/cc APPROX.
VISCOSITY:	20.000-30.000 C.P.S.
TACT DRYING:	30 MIN APPROX.
PERFORMANCE:	6-8 m ² /l DEPENDING ON SURFACE CONDITIONS
COVERING UP:	>90%
RE-PAINTING:	AFTER 2-4 HOURS
PACKAGING:	3 & 14 LTRS IML PLASTIC
WAREHOUSING:	EXCELLENT IN ITS CLOSED ORIGINAL PACKAGE IN NORMAL CONDITIONS & TEMPERATURES

PROPERTIES:

EXCELLENT APPLICATION WITH BRUSH AND ROLLER OFFERING AN EXCELLENT FINISHING. ONCE DRY, STAND OUT DUE TO ITS HIGH COVERING UP AND WHITENESS. CAN BE APPLY ON INTERNAL SURFACES IN GOOD CONDITIONS.

APPLICATIONS:

FOR THE PROFESSIONAL USE AND APPROPRIATE FOR THE RIGHT DECORATION WHERE A PERFECT FINISHING IS REQUIRED.

USE METHOD:

TO BE APPLIED ON CLEAN AND DRY SURFACES W/O DUST, GREASE, HUMIDITY, RUST, SALTPETRE, ETC. SURFACES WITH OLD OR IN BAD CONDITION PAINTS MUST BE TOTALLY CLEAN TO ENSURE THE RIGHT ADHESIVENESS. DO NOT APPLY AT TEMPERATURES BELLOW 5°C OR OVER 35°C.

REV. 02.06.11

With this technical card, based on our experience and research, we only pretend to inform and advise you according to our knowledge and good faith, In any case we can not be responsables for the use of this product under circumstances and conditions of its application, due to be out of our own control.

. Crta. Nacional 301- km.215.700
02630 La Roda (Albacete) Spain
Ph.: +34 967 44 38 38- Fax: +34 967 44 38 14
info@pinturasadoral.com
www.pinturasadoral.com