



3 DIAMONDS MATTE

PRODUCT DESCRIPTION:

MATTE PLASTIC PAINT BASED ON ACRYLIC RESINS IN WATERY SPREAD AND HIGH RESISTANT AND STRENGTH TO THE LIGHT PIGMENTS. USED BY THE PROFESSIONAL IN EXTERNAL AND INTERNAL SURFACES UNDER A LOW AGGRESSIVE ATMOSPHERIC CONDITIONS AND DEPENDING FROM THE WEATHER CONDITIONS.

TECHNICAL CHARACTERISTICS:

COLOUR:	WHITE
FINISHING:	MATTE
DILUTE:	WATER
DENSITY:	1,6 gr/c.c. APPROX.
VISCOSITY:	20.000-30.000 C.P.S.
TACT DRYING:	30 MIN. APPROX.
PERFORMANCE:	5-7 m ² / LTS ACORDING SURFACE CONDITION
COVERING UP:	>90%
RE-PAINTING:	AFTER 2-4 HOURS
VISCOSITY:	30.000 CENTIPOISE 5, BROOKFIELD, Sp-6,10 r.p.m. 23°C
WASHABILITY:	EXCELLENT ACCORDING TO DIN 53778 SPECIFICATION
PACKAGING:	750 ML, 3, 9 & 14 LTS IML PLASTIC
WAREHOUSING:	EXCELLENT IN ITS ORIGINAL CLOSED PACKAGE UNDER NORMAL TEMPERATURES AND HUMIDITY

PROPERTIES:

MATTE PAINT PRESENTING A HIGH WHITENESS GRADE, PERFORMANCE AND COVERING UP.

APPLICATIONS:

VERY APPROPRIATE FOR INTERNAL AND EXTERNAL DECORATION AND PROTECTION CONSTRUCTION SURFACES SUBMITTED AT LOW AGGRESSIVE ATMOSPHERIC CONDITIONS. OFFER A VERY DECORATIVE MATTE FINISHING.

USE METHOD:

CAN BE APPLIED WITH BRUSH ROLLER OR AIRLESS GUN ON CLEAN AND DRY SURFACES W/O DUST, RUST, GREASE, HUMIDITY, SALTPETRE, ETC. OLD PAINTS IN SURFACES MUST BE REMOVED AND TATALLY CLEAN TO ENSURE ITS RIGHT AND PERFECT ADHESIVENESS. DO NOT APPLY AT TEMPERATURES BELLOW 5°C OR OVER 35°C.

REV. 02.06.11

With this technical card, based on our experience and research, we only pretend to inform and advise you according to our knowledge and good faith, In any case we can not be responsables for the use of this product under circumstances and conditions of its application, due to be out of our own control.

. Crta. Nacional 301- km.215.700
02630 La Roda (Albacete) Spain
Ph.: +34 967 44 38 38- Fax: +34 967 44 38 14
info@pinturasadoral.com
www.pinturasadoral.com