



---

# BLACK EXTRA MATTE

## PRODUCT DESCRIPTION:

TECHNICALLY BALANCED MATTE PLASTIC PAINT, BASED ON ACRYLIC RESINS IN WATERY SPREAD AND HIGH RESISTANCE AND STRENGTH TO THE LIGHT PIGMENTS, OFFERING A VERY BLACK, COVERING UP AND WASHABLE FINISHING. VERY APPROPRIATE FOR INTERNAL AND EXTERNAL USE. RESSISTANT TO THE ATMOSPHERIC AGENTS. NOT FLAMMABLE PRODUCT.

## TECHNICAL CHARACTERISTICS:

COLOUR:	BLACK
FINISHING:	MATTE
DILUTE:	WATER
DENSITY:	1.6 gr/cc APPROX
VISCOSITY:	20.000-30.000 C.P.S.
TACT DRYING:	30 MIN APPROX
PERFORMANCE:	9-11 m <sup>2</sup> /l DEPENDING ON SURFACE CONDITIONS
COVERING UP:	100%
WASHABILITY:	EXCELLENT ACCORDING TO DIN 53778 SPECIFICATION
WAREHOUSING:	18 MONTHS. EXCELLENT IN ITS ORIGINAL CLOSED PACKAGE AT NORMAL HUMIDITY & TEMPERATURES
PACKAGING:	750 ML, 3 & 14 LTS IML PLASTIC
RE-PAINTING:	AFTER 2-4 HOURS

## PROPERTIES:

EXCELLENT APPLICATION WITH BRUSH AND ROLLER OFFERING AN EXCELLENT FINISHING AND COVERING UP. RESISTANT TO ABRASION, HUMID RUB AND ALKALINITY.

## APPLICATIONS:

VERY APPROPRIATE FOR INTERNAL AND EXTERNAL SURFACES DECORATION, PROTECTION AND PRESERVATION.

## USE METHOD:

APPLY ON CLEAN AND DRY SURFACES, W/O DUST, RUST, GREASE, HUMIDITY, SALTPETRE, ETC. OLD PAINTS MUST BE REMOVED AND TOTALLY CLEANED TO GUARANTEE THE RIGHT ADHESIVENESS. DO NOT APPLY AT TEMPERATURES BELOW 5°C OR OVER 35°C

REV. 02.06.11

---

*With this technical card, based on our experience and research, we only pretend to inform and advise you according to our knowledge and good faith, In any case we can not be responsables for the use of this product under circumstances and conditions of its application, due to be out of our own control.*

---

. Crta. Nacional 301- km.215.700  
02630 La Roda (Albacete) Spain  
Ph.: +34 967 44 38 38- Fax: +34 967 44 38 14  
[info@pinturasadoral.com](mailto:info@pinturasadoral.com)  
[www.pinturasadoral.com](http://www.pinturasadoral.com)