



---

# MAX COVER MATTE

## PRODUCT DESCRIPTION:

GOOD QUALITY MATTE PLASTIC PAINT, BASED ON ACRYLIC RESINS IN WATERY SPREAD AND STRONG RESISTANCE AND STRENGTH TO THE LIGHT PIGMENTS. OFFERING WASHABLE, RESISTANT AND COVERING UP FINISHING. HIGH WHITENESS GRADE AND PERFORMANCE.

## TECHNICAL CHARACTERISTICS:

COLOUR:	WHITE
FINISHING:	MATTE
DILUTE:	WATER
DENSITY:	1.6 gr/cc APPROX
VISCOSITY:	20.000-30.000 C.P.S.
TACT DRYING:	30 MIN APPROX
RE-PAINTING:	2-4 HOURS
PERFORMANCE:	8-10 m <sup>2</sup> /l/LAYER DEPENDING ON SURFACE CONDITIONS
COVERING UP:	>90%
WASHABILITY:	EXCELLENT ACCORDING TO DIN 53778 SPECIFICATION
WAREHOUSING:	18 MONTHS EXCELLENT IN ITS ORIGINAL CLOSED PACKAGE AT NORMAL TEMPERATURES
PACKAGING:	3, 9 & 14 LTS IML LITHOGRAPHED

## PROPERTIES:

HIGH COVERING UP AND WHITENESS PAINT. EXCELLENT APPLICATION WITH BRUSH AND ROLLER OFFERING AN EXCELLENT FINISHING. RESSISTANT TO ABRASION, HUMID, RUB AND ALKALINITY.

## **APPLICATIONS:**

APPROPRIATE FOR DECORATION, PROTECTION AND PRESERVATION ON INTERNAL AND EXTERNAL BUILDING SURFACES UNDER LOW AGGRESSIVE ATMOSPHERIC CONDITIONS. OFFER A VERY DECORATIVE MATTE FINISHING.

## **USE METHOD:**

APPLY WITH BRUSH, ROLLER OR AIRLESS GUN, ON CLEAN AND DRY SURFACES, W/O DUST, RUST, GREASE, HUMIDITY, SALTPETRE, ETC. OLD PAINTS MUST BE REMOVED AND TOTALLY CLEANED TO GUARANTEE THE RIGHT ADHESIVENESS. DO NOT APPLY AT TEMPERATURES BELLOW 5°C OR OVER 35°C

REV. 02.06.11

---

*With this technical card, based on our experience and research, we only pretend to inform and advise you according to our knowledge and good faith, In any case we can not be responsables for the use of this product under circumstances and conditions of its application, due to be out of our own control.*

---

. Crta. Nacional 301- km.215.700  
02630 La Roda (Albacete) Spain  
Ph.: +34 967 44 38 38- Fax: +34 967 44 38 14  
[info@pinturasadoral.com](mailto:info@pinturasadoral.com)  
[www.pinturasadoral.com](http://www.pinturasadoral.com)