



PROFESSIONAL MATTE

PRODUCT DESCRIPTION:

GOOD QUALITY MATTE PLASTIC PAINT, BASED ON ACRYLIC RESINS IN WATERY SPREAD AND STRONG RESISTANCE AND STRENGTH TO THE LIGHT PIGMENTS. OFFERING VERY WHITE, WASHABLE, RESISTANT AND COVERING UP FINISHING. FOR PROFESSIONAL USE IN EXTERNAL AND INTERNAL PURPOSES.

TECHNICAL CHARACTERISTICS:

COLOUR:	WHITE
FINISHING:	MATTE
DILUTE:	WATER
DENSITY:	1.66 gr/cc APPROX
VISCOSITY:	20.000-30.000 C.P.S.
TACT DRYING:	30 MIN APPROX
PERFORMANCE:	7-9 m ² /l/LAYER DEPENDING ON SURFACE CONDITIONS
COVERING UP:	>90%
WASHABILITY:	EXCELLENT ACCORDING TO DIN 53778 SPECIFICATION
WAREHOUSING:	18 MONTHS AT NORMAL TEMPERATURES
PACKAGING:	750 ML, 3, 9 & 14 LTS IML PLASTIC

PROPERTIES:

HIGH COVERING UP AND WHITENESS PAINT. EXCELLENT APPLICATION WITH BRUSH AND ROLLER OFFERING AN EXCELLENT FINISHING. RESSISTANT TO ABRASION, HUMID, RUB AND ALKALINITY.

APPLICATIONS:

APPROPRIATE FOR DECORATION, PROTECTION AND PRESERVATION ON INTERNAL AND EXTERNAL BUILDING SURFACES UNDER LOW AGGRESSIVE ATMOSPHERIC CONDITIONS.

USE METHOD:

APPLY WITH BRUSH, ROLLER OR AIRLESS GUN, ON CLEAN AND DRY SURFACES, W/O DUST, RUST, GREASE, HUMIDITY, SALTPETRE, ETC. OLD PAINTS MUST BE REMOVED AND TOTALLY CLEANED TO GUARANTEE THE RIGHT ADHESIVENESS. DO NOT APPLY AT TEMPERATURES BELLOW 5°C OR OVER 35°C

REV. 02.06.11

With this technical card, based on our experience and research, we only pretend to inform and advise you according to our knowledge and good faith, In any case we can not be responsables for the use of this product under circumstances and conditions of its application, due to be out of our own control.

. Crta. Nacional 301- km.215.700
02630 La Roda (Albacete) Spain
Ph.: +34 967 44 38 38- Fax: +34 967 44 38 14
info@pinturasadoral.com
www.pinturasadoral.com