



---

# SEMI MATTE

## **PRODUCT DESCRIPTION:**

SEMI MATTE PLASTIC PAINT TECHNICALLY VERY BALANCED, BASED ON ACRYLIC RESINS IN WATERY SPREAD AND HIGH RESISTANCE AND STRENGTH TO THE LIGHT PIGMENTS. GREAT QUALITY OFFERING VERY WHITE, COVERING UP AND WASHABLE FINISHING. VERY APPROPRIATE FOR INTERNAL AND EXTERNAL APPLICATIONS. VERY RESISTANT TO THE ATMOSPHERIC AGENTS. NOT FLAMABLE PRODUCT.

## **TECHNICAL CHARACTERISTICS:**

COLOUR:	WHITE
FINISHING:	SEMI-MATTE
DILUTE:	WATER
DENSITY:	1,6 gr/cc
VISCOSITY:	20.000-30.000 C.P.S.
TACT DRYING:	30 MIN APPROX
PERFORMANCE:	8-10 m <sup>2</sup> /l DEPENDING ON SURFACE CONDITION
COVERING UP:	>90%
RE-PAINTING:	AFTER 2-4 HOURS
WASHABILITY:	EXCELLENT ACCORDINT TO DIN 53778 SPECIFICATION
PACKAGING:	750 ML, 3, 9 & 14 L IML PLASTIC
WAREHOUSING:	18 MONTHS IN NORMAL TEMPERATURE & CONDITIONS

## **PROPERTIES:**

EXCELLENT APPLICATION WITH BRUSH AND ROLLER OFFERING AN EXCELLENT FINISHING, VERY RESISTANT TO ABRASION, HUMID RUB AND ALKALINITY.

## **APPLICATIONS:**

REOCMENDED FOR DECORATION, PROTECTION AND PRESERVATION OF INTERNAL AND EXTERNAL SURFACES.

## **USE METHOD:**

APPLY ON CLEAN AND DRY SURFACES W/O RUST, DUST, GREASE, HUMIDITY AND SALTPETRE. OLD PAINTS MUST BE TOTALLY REMOVED FROM THE SURFACES TO ENSURE THE RIGHT ADHESIVENESS. DO NOT APPLY AT TEMPERATURES BELOW 5°C OR OVER 35°C.

REV. 02.06.11

---

*With this technical card, based on our experience and research, we only pretend to inform and advise you according to our knowledge and good faith, In any case we can not be responsables for the use of this product under circumstances and conditions of its application, due to be out of our own control.*

---

. Crta. Nacional 301- km.215.700  
02630 La Roda (Albacete) Spain  
Ph.: +34 967 44 38 38- Fax: +34 967 44 38 14  
[info@pinturasadoral.com](mailto:info@pinturasadoral.com)  
[www.pinturasadoral.com](http://www.pinturasadoral.com)