



SUPER MATTE

PRODUCT DESCRIPTION:

HIGH QUALITY MATTE PLASTIC PAINT BASED ON ACRYLIC-STYRENE RUBBER RESINS AND HIGH RESISTANCE AND STRENGTH TO THE LIGHT PIGMENT, OFFERING A VERY WHITE, COVERING UP AND WASHABLE FINISHING BEING VERY APPROPRIATE FOR INTERNAL AS FOR EXTERNAL USES.

TECHNICAL CHARACTERISTICS:

COLOUR:	WHITE
FINISHING:	MATTE
DILUTE:	WATER
DENSITY:	1.6 gr/cc
VISCOSITY:	20.000-30.000 C.P.S.
TACT DRYING:	30 MIN APPROX
PERFORMANCE:	9-12 m ² /l DEPENDING ON SURFACE CONDITIONS
COVERING UP:	>90%
RE-PAINTING:	AFTER 2-4 HOURS
WASHABILITY:	EXCELLENT ACCORDING TO DIN 53778 SPECIFICATION
PACKAGING:	750 ML, 3, 9 & 14 L IML PLASTIC
WAREHOUSING:	18 MONTHS IN NORMAL CONDITIONS AND TEMPERATURE

PROPERTIES:

EXCELLENT APPLICATION WITH BRUSH AND ROLLER OFFERING AN EXCELLENT FINISHING. RESISTANT TO ABRASION, HUMID RUB AND ALKALINITY.

APPLICATIONS:

FOR PROFESSIONAL USE VERY APPROPRIATE FOR THE DECORATION, PROTECTION AND PRESERVATION OF INTERNAL AND EXTERNAL SURFACES AND RESISTANT TO THE ATMOSPHERIC AGENTS.

USE METHOD:

APPLY ON CLEAN AND DRY SURFACES W/O DUST, RUST, GREASE, HUMIDITY, SALTPETRE, ETC. OLD PAINTS MUST BE TOTALLY REMOVED TO ENSURE THE RIGHT ADHESIVENESS. DO NOT APPLY AT TEMPERATURES BELLOW 5°C OR OVER 35°C.

REV. 02.06.11

With this technical card, based on our experience and research, we only pretend to inform and advise you according to our knowledge and good faith, In any case we can not be responsables for the use of this product under circumstances and conditions of its application, due to be out of our own control.

. Crta. Nacional 301- km.215.700
02630 La Roda (Albacete) Spain
Ph.: +34 967 44 38 38- Fax: +34 967 44 38 14
info@pinturasadoral.com
www.pinturasadoral.com